

TRANSGLOSS INSTRUCTIONS

FOR CREATING A GLOSSY FINISH...
ON OUR DIGITAL TRANSFERS (InkJet or Laser Transfers)

After printing your transfer on one of our heat transfer papers...
(ie: TransferJet, PremiumPlus, or High Temp Laser) You will apply this TransGloss product to the pre-printed transfer after the printed transfer is on the shirt.

NOTES:

- 1) **YOU DO NOT PRINT ON THIS TRANSGLOSS PRODUCT!**
- 2) A conventional **home iron will not** provide a satisfactory image transfer. You must use a heat press.

First follow the directions that come with the digital heat transfer paper (ie: TransferJet, PremiumPlus, or High Temp Laser) that you are going to print on. Then follow the rest of the below instructions:

Applying TransGloss:

(After applying your printed transfer to the shirt)

- Place TransGloss paper (gloss side facing down) on top of the printed transfer
- Set heat press to medium pressure (approx. 40 lbs. of pressure). Press should snap closed firmly.
- Transfer at 360°F for 5 - 8 seconds.
- **Peel COLD!**

Washing

- Turn garment inside out. Machine wash in warm or cold water.
- Do not use softener or bleach.
- Tumble dry on low setting. ***Do not dry clean!***
- To brighten image on fabric after washing, press with an iron or heat press on medium setting. Make sure you cover image with Teflon sheet to protect iron/heat press.

IMPORTANT: Please keep your Transgloss paper in plastic bag until actual use.

This will keep moisture out of the paper. Close the bag after each use.

Note: Gloss finish may wear after repeat washing. See above wash instructions

www.BESTBLANKS.com

954-989-1250