

IMAGE CLIP® Laser Dark Heat Transfer Paper

IMAGE CLIP® Laser Dark Heat Transfer Papers are designed for the heat transfer of full color images with oil or oil-less laser color copiers or color laser printers to dark and bright colored items including: T-shirts, handbags, mouse pads, coasters, leather articles, art papers, etc. IMAGE CLIP® Laser Dark works well on cotton, 50-50 blends and polyester. There is no need to trim the paper. IMAGE CLIP® Transfer Paper is self-weeding and leaves no background plastic polymer. Choose fabrics with a tight weave.

IMPORTANT: Make one shirt and wash it by itself before producing your order. This will help you from making costly mistakes and will allow you to take corrective action before you make a quantity of shirts. When the instructions are followed you will get excellent results!

PRINTING

1. Mirror the image.
2. Laser print the coated side of the paper identified as the Imaging Sheet.
3. IMAGE CLIP® Laser Dark Paper should be fed into the copier or printer with the short dimension first (grain long). For best fusing results use a heavy paper setting.

TRANSFER

Use Commercial Heat Press

1. Marry the imaged sheet with the transfer sheet. This will apply the transfer coating to the imaged area.
Press: 20 seconds at 250F using heavy pressure
Separate the papers while still hot.
2. Place the imaging sheet face down onto the shirt or other substrate.
Press: 25 seconds at 375F using heavy pressure
Cool before peeling. Stretch immediately after peeling if desired.



LASER
RUNS IN MOST NEWER
TECHNOLOGY OIL OR
OIL-LESS PRINTERS



**DARK and
BRIGHT COLORS**



NO HAND IRON

WASHING INSTRUCTIONS

Turn garment inside out and wash in cold water using a mild detergent. Do not use bleach. Dry on low heat setting. Do not iron directly on the transferred area.

STORAGE AND HANDLING OF IMAGE CLIP® HEAT TRANSFER PAPERS

Store in a cool, dry area and do not remove from carton or poly bag until you are ready to use.

1st Pressing	
TEMPERATURE	250°
PRESSURE	Heavy
TIME	20 seconds

2nd Pressing	
TEMPERATURE	375°
PRESSURE	Heavy
TIME	25 seconds

IMPORTANT

We thoroughly test each of our products on various substrates using different transfer equipment. However, it is impossible for us to duplicate all variables using all substrates and transfer equipment. Therefore, it is essential that you test the paper prior to production using your equipment, methods, and substrate material. Heat presses vary in accuracy. Conduct tests to determine the best time and temperature to use with your equipment. Please keep in mind that the Seller's and Manufacturer's maximum obligation shall be to replace any paper that has proven to be defective. Neither the Seller nor the Manufacturer shall be liable for any injury, direct or consequential, arising out of the use of, or inability to use this paper.

Your One Stop Source!

www.BestBlanks.com

1-888-431-7385 954-989-1250